

VG930m

19" DIGITAL MEDIA GRAPHIC SERIES LCD

WITH SWIVEL AND HEIGHT ADJUST

Stylish, multimedia performance.

The ViewSonic® 19" VG930m delivers multimedia performance to your desktop in a stylish, slim design. It's an ideal choice for business applications that include mixed data, audio, graphics and video content. Graphics professionals and gamers will love the FAST 8MS VIDEO RESPONSE that delivers blur-free, full motion video and crystal-clear graphics rendering. OPTISYNC® ANALOG AND DIGITAL INPUTS ensure seamless compatibility with VGA and digital DVI sources. VESA® wall mount-compliance and the INTEGRATED AMP AND STEREO SPEAKERS reduce desktop clutter while accenting your office décor. The Kensington® security port offers theft deterrence and the OSD/Power lock ensures your optimal screen settings remain in place.



FAST VIDEO RESPONSE FOR INTENSE GRAPHICS

- > **ClearMotiv™ 8ms video response time**
Fast 8ms video response delivers broadcast-quality video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **OptiSync® digital/analog inputs expand your connectivity**
Multi-mode input technology supports both digital (DVI) and analog (VGA) signals for ultimate compatibility and configuration flexibility.
- > **Ergonomic base adds ease and comfort**
Ultimate ergonomic flexibility comes built-in with the convenient 3.2" height adjustment and 360° swivel.
- > **Multimedia enhanced**
Save workspace and enjoy rich, stereo sound with two built-in stereo speakers.
- > **Stylish slim-bezel design**
The full 19" viewable screen in an ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > **High 280 nit brightness (typ) and 600:1 contrast ratio (typ)**
- > **VESA® 100mm wall mount interface and Kensington® security port**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 

the choice of professionals

VG930m

19" DIGITAL MEDIA GRAPHIC SERIES LCD WITH SWIVEL AND HEIGHT ADJUST



360° SWIVEL



HEIGHT ADJUST



TILT



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

LCD	Type	19" color TFT active matrix SXGA LCD
	Display Area	14.8" horizontal x 11.9" vertical; 19.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	600:1 (typ)
	Viewing Angles	160° horizontal, 155° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	280 cd/m2 (typ)
	Panel Surface	Anti-glare
VIDEO INPUT	Analog/Digital	RGB analog (75 ohms, 0.7 Vp-p)/DVI-D
	Frequency	F _H : 30~82kHz, F _V : 50~75Hz
	Sync	H/V separated (TTL)
COMPATIBILITY	PC	VGA up to 1280x1024 non-interlaced
	Mac®*	Power Mac™ G3/G4/G5 up to 1280x1024
CONNECTOR	Analog/Digital	15-pin mini D-sub/DVI-D
	Audio In	Stereo mini audio line in
	Power	3-pin AC plug
POWER	Voltage	AC 100~240V (universal), 50~60Hz (auto switch)
	Consumption	35W (typ)
AUDIO	Speakers	2x1.5-watt
	Amplifier	1.5-watt
CONTROLS	Basic	Power, 1, down, up, 2, mute, volume +/-
	OnView®	Auto image adjust, brightness, contrast, input selection, ViewMatch® color adjust (sRGB, 9300K, 6800K, 6500K), information (mode, model number, serial number), audio (volume, mute), manual image adjust (H. position, V. position, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), memory recall
ERGONOMICS		Height adjustment range 3.2", tilt, swivel range 360°
OPERATING CONDITIONS	Temperature	41~95°F (5~35°C)
	Humidity	20~80% (non-condensing)
DIMENSIONS (W x H x D)	Physical (mm)	428mm x 479mm x 230mm (with stand) 428mm x 399mm x 68mm (without stand)
	Physical (in.)	16.8" x 18.9" x 9.1" (with stand) 16.8" x 15.5" x 2.6" (without stand)
WEIGHT	Net	13.3 lb. (6.0 kg) (with stand)
	Gross	16.0 lb. (7.2 kg) (with stand)
REGULATIONS		UL, cUL, FCC-B, CB, CE, ENERGY STAR®, NOM, TUV/GS, TUV-S, TUV/ERGO (covers ISO13406-2 & MPR II), TCO'03, GOST-R + 20 original copies hygienic, SASO, PCBC, VCCI, BSMI, CCC, PSB, C-TICK, RoHS
POWER MANAGEMENT		Meets TCO'03 and ENERGY STAR® standards
PACKAGE CONTENTS		LCD display, VGA cable, power cable, audio cable, Quick Start Guide, ViewSonic Wizard CD
WARRANTY		Three-year limited warranty

ViewSonic

the choice of professionals

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [13107-00B-08/06] VG930m-3

For more product information, visit us on the web at ViewSonic.com