

# VA903b

## 19" VALUE SERIES LCD DISPLAY

WITH 8MS VIDEO RESPONSE

## High quality, high performance.

ViewSonic's 19" VA903b LCD is a big screen performer that's great for intensive graphics work and even for entertainment. Fast 8ms video response time delivers crystal-clear graphics and smooth, full-motion video for viewing movies, sports and scrolling text. With 700:1 contrast ratio (typ) and 300 nits of brightness (typ) the VA903b displays brilliant colors. Lock in those brilliant colors and your perfect screen adjustment with the OSD and power lock. Add a touch of style to your workspace by mounting the stylish, VESA® wall-mount compliant, slim bezel on your wall. The Kensington® security port offers theft deterrence. Prepare to be impressed by the performance, style and quality of the VA903b.



### IMPRESSIVE PERFORMANCE WITHOUT THE HIGH PRICE TAG

- > Fast 8ms video response delivers superior picture clarity
- > Dynamic Structure™ technology  
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > High brightness and contrast ratio  
300-nit brightness (typ) and 700:1 contrast ratio (typ) for rich, detailed images.
- > 1280x1024 optimum resolution  
Incredible image detail for sharp text and graphics.
- > Stylish slim-bezel design  
An ultra-thin bezel lets you see more without taking up valuable desktop real estate.
- > OnView® controls for superior screen adjustability  
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > OSD/Power lock secures your settings  
Prevents changes to monitor settings and maintains an optimized image.
- > Integrated power supply
- > VESA® 100mm wall-mount compliant
- > TCO'03 and ENERGY STAR® qualified
- > PC and Mac® compatible
- > 24/7 free technical and customer support.\*



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic**   
the choice of professionals

# VA903b

## 19" VALUE SERIES LCD DISPLAY WITH 8MS VIDEO RESPONSE



<b>LCD</b>	Type	19" color TFT active matrix SXGA LCD
	Display Area	14.8" horizontal x 11.9" vertical; 19.0" diagonal
	Optimum Resolution	1280x1024
	Contrast Ratio	700:1 (typ)
	Viewing Angles	160° horizontal, 160° vertical @ contrast ratio > 5:1
	Response Time	8ms (typ)
	Light Source	Long life, 50,000 hrs. (typ)
	Brightness	300 cd/m2 (typ)
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analog	RGB analog (75 ohms, 0.7 Vp-p)
	Frequency	F <sub>H</sub> : 30~82kHz, F <sub>V</sub> : 50~85Hz
	Sync	H/V separated (TTL)
<b>COMPATIBILITY</b>	PC	VGA up to 1280x1024 non-interlaced
	Mac <sup>®</sup> **	Power Mac™ G3/G4/G5 up to 1024x768
<b>CONNECTOR</b>	Analog	15-pin mini D-sub
	Power	3-pin AC plug
<b>POWER</b>	Voltage	AC 100~240V (universal), 50/60Hz (auto switch)
	Consumption	33W (typ)
<b>CONTROLS</b>	Basic	Power, 1, down, up, 2
	OnView <sup>®</sup>	Auto image adjust, brightness, contrast, input selection, ViewMatch <sup>®</sup> color adjust (sRGB, 9300K, 6500K, 5400K), information (mode, model number, serial number), manual image adjust (H. position, V. position, fine tune, sharpness), language, resolution notice, OSD position, OSD timeout, OSD background, memory recall
<b>OPERATING CONDITIONS</b>	Temperature	32~104°F (0~40°C)
	Humidity	20~90% (non-condensing)
<b>DIMENSIONS (W x H x D)</b>	Physical (mm)	416mm x 428mm x 210mm
	Physical (in.)	16.4" x 16.9" x 8.3"
<b>WEIGHT</b>	Net	10.8 lb. (4.9 kg)
	Gross	15.2 lb. (6.9 kg)
<b>REGULATIONS</b>		UL, cUL, FCC-B, CB, CE, ENERGY STAR <sup>®</sup> , NOM, TUV/GS, TUV/ERGO, TCO'03, BSMI, CCC, PSB, C-TICK, RoHS, WEEE
<b>POWER MANAGEMENT</b>		Meets TCO'03 and ENERGY STAR <sup>®</sup> standards
<b>PACKAGE CONTENTS</b>		LCD display, video cable, power cable, Quick Start Guide, ViewSonic Wizard
<b>WARRANTY</b>		Three-year limited warranty on parts, labor and backlight



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

**ViewSonic** 

*the choice of professionals*

ViewSonic Corporation • 381 Brea Canyon Road, Walnut, CA 91789

Customer Service and Technical Support: (800) 688-6688 • Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

\*Excluding major U.S. holidays. \*\*Adapter may be required. Analog adapter available from ViewSonic. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2006 ViewSonic Corporation. All rights reserved. [12966-00B-04/06] VA903b-2

For more product information, visit us on the web at [ViewSonic.com](http://ViewSonic.com)